

Ref:FN1-BV1W-2L
Rev.:Initial
Page:1/1

BUTTERFLY VALVE WITH HANDLE FN1-BV1W-2L



FTV
Since 2000

APPLICATION

General Use: Water, sea water, gas, pressurized air, acids etc.

CARACTERISTIQUES GENERALES

Resilient Seat Wafer Type Butterfly Valves
Design according with BS EN593/API609
Testing according with EN598. For Shell: 1.5 times Sealing: 1.1 times.
Tightness in both ways. wafer type with smooth ears. Resilient seat adapted to the shape of the body assures low operating torque. Mounting flange according to ISO5211

CONSTRUCTION

NO.	PARTS	MATERIAL
1	BODY	CI / DI
2	SEAT	EPDM / NBR / VITON / SILICON
3	STEM	SS416 / 316 / 304
4	DISC	DI / CF8 / CF8M
5	BUSHING	PTFE / BRONZE
6	O-RING	NBR / EPDM
7	BUSHING	PTFE / BRONZE
8	BOLT&NUT	STAINLESS STEEL / GALVANIZED
9	FLAT WASHER	STAINLESS STEEL / GALVANIZED
10	BOLT	STAINLESS STEEL / GALVANIZED
11	PRESSURE RING	CARBON STEEL
12	GEAR DISC	CARBON STEEL / ALUMINUM
13	HAND SHANK	MALLEABLE IRON / AL / SS



DIMENSIONS

DN		A	B	L	PN10			PN16			ANSI 150		
mm	inch				ΦD	N	M	ΦD	N	M	ΦD	N	M
50	2"	161	80	43	125	4	Φ18	125	4	Φ18	120.5	4	Φ19
65	2.5"	175	89	46	145	4	Φ18	145	4	Φ18	139.5	4	Φ19
80	3"	181	95	46	160	8	Φ18	160	8	Φ18	152.5	4	Φ19
100	4"	200	114	52	180	8	Φ18	180	8	Φ18	190.5	8	Φ19
125	5"	213	127	56	210	8	Φ18	210	8	Φ18	216	8	Φ22
150	6"	226	139	56	240	8	Φ22	240	8	Φ22	241.5	8	Φ22
200	8"	260	175	60	295	8	Φ22	295	12	Φ22	298.5	8	Φ22
250	10"	292	203	68	350	12	Φ22	355	12	Φ26	362	12	Φ25
300	12"	337	242	78	400	12	Φ22	410	12	Φ26	432	12	Φ25

WORKING CONDITIONS

Maximum Working Pressure: 16 bar.
Maximum Working Temperature table

Sleeve type in option	Maximum Temperature	Peak Temperature
EPDM	+4°C~+110°C	-20°C~+130°C
EPDM Blanc	+4°C~+110°C	-20°C~+130°C
CSM (Type Hypalon)	+4°C~+80°C	-20°C~+110°C
FPM (Type Viton)	-10°C~+170°C	-20°C~+200°C
Silicone	-20°C~+170°C	-40°C~+200°C
Nitrile (NBR)	-10°C~+80°C	-20°C~+90°C



STANDARDS

Manufacture according to the requirements of the European directive 2014/68/EU, modulate H Face to face according to standards NF EN558 SERIE 20, ISO5752, DIN3202.
Mounting between flanges UNI EN1092:PN10/16, ANSI150, JIS 5K/10K, BS 10, TABLE E etc.
Body: 24 bar
Seat: 17.6 bar

Tianjin Fortis Valve Co., Ltd.
Fortis Valve-Guaizigou Industrial Zone, Xiaozhan Town, Jin nan District, Tianjin of China.
Tel: +86-22-88529757 Fax: +86-22-88818118
Email: info@fortisvalves.com Web: www.fortisvalves.com